



# Micro-COB-63J Series Product Specification

Micro-COB-63J Series  
Full Flip Chip COB  
Indoor Fine Pixel Pitch LED Display

APPROVE	CHECK	DRAW
General Office	R&D	P.D
Dai Zhiming	Zeng Yinhai	Yi Wei
Version NO: V1.1		
Release Date: 2023-4-20		



# Micro-COB-63J Series

Full Flip Chip COB Indoor Fine Pixel Pitch LED Display



**Efficient Heat  
Dissipation**



**Low Power  
Consumption**



**High  
Protection**



**Dual  
Redundancy**



**Easy  
Maintenance**

## Product Overview

The 63J series is a self-developed ultra-high-definition product targeting the fine-pitch LED display market. It is mainly used in various control fields such as security monitoring, command dispatch, video conferencing, and broadcasting for high-quality display applications.

## Product Features

- **Efficient Heat Dissipation:** High precision seamless splicing, silent and fanless design, die-cast aluminum body;
- **Low Power Consumption:** Common cathode circuit design, achieving energy-saving and low power consumption, high refresh rate, HDR high dynamic image display, 16-bit high grayscale and low brightness;
- **High Protection:** Full flip-chip COB integrated packaging, high protection, high reliability, high environmental adaptability;
- **Dual Redundancy:** Supports dual backup for power and signal;
- **Easy Maintenance:** Full front maintenance, featuring hot-swappable modules, and overall rigid connection.




# Specification

Name	Category	63J
<b>Module Parameter</b>	Pixel Structure	COB
	Pixel Pitch (mm)	1.56
	Module Size (mm)	150x168.75
	Module Resolution (W×H)	96*108
<b>Cabinet Parameter</b>	Unit Composition (W×H)	4*2
	Cabinet Size (mm)	600x337.5x28
	Cabinet Resolution (W×H)	384*216
	Dimension (m <sup>2</sup> )	0.2025
	Pixel Density (Dots/m <sup>2</sup> )	409600
	Material	Die-cast Aluminum
	Cabinet Weight (kg)	4.7Kg
	Cabinet Flatness	≤0.1mm
<b>Optics Parameter</b>	Brightness	0-1000cd/m <sup>2</sup> (adjustable)
	Color Temperature (K)	2000~12000 (adjustable)
	Viewing Angle (H/V)	170°/170°
	Center Distance Deviation of Luminescent Point	<3%
	Luminance Uniformity	≥98%
	Color Uniformity	Within ±0.0035 Cx, Cy
	Contrast Ratio	1000000:1
<b>Electric Parameter</b>	Peak Power Consumption	≤500W/m <sup>2</sup> (Tested at 600 nits white balance)
	Average Power Consumption	200W/m <sup>2</sup>
	Power Supply	AC100~240V (50~60Hz)
<b>Process performance</b>	Driving Mode	Constant current drive
	Frame Frequency	50/60Hz
	Refresh Rate	3840Hz
	Gray Scale	14bit
<b>Application Parameter</b>	Operating Temperature	-20°C~+60°C
	Operating Humidity	10%~90%RH anti-fog
	Service Life	≥100,000Hrs
	Maintenance Mode	Full Front maintenance
	Protection Grade	IP54
	Certification Type	CCC、CE、FCC



Note 1: According to customer requirements, different item parameters will be slightly different, and the above parameters are just for reference;

Note 2: Due to the batch nature of product production, there may be a deviation of approximately 5%-10% in terms of brightness, power consumption, and other parameters. The specific parameters are based on actual situation.

## Product Drawing



## Product Package

		
	Module Package↑	Cabinet Package↑
Quantity	4*4*36=576pcs	6*1*8=48pcs
Net Weight	3.9Kg/140.4Kg	23.2Kg/185.6Kg
Gross Weight	4.75kg/171Kg	27Kg/216kg
Dimension (Individual carton)	443mm×353mm×133mm	665mm×297mm×410mm
Dimension (Overall wooden crate)	1390mm×820mm×900mm	1390mm×820mm×900mm